

for situational awareness

— no hearing protection

FIRECOM 50 SERIES WIRED

UH-51S UNDER-HELMET STYLE HEADSET

The Firecom UH-51S wired headset delivers all the benefits of hands-free, full-duplex communication with your crew. Operating with a stand-alone intercom system or integrated with a mobile radio, the flexible design brings all crew members into constant communication. Behind-the-head band configuration with adjustable over-head strap easily accommodates use with helmets. Water-resistant and comfortable ear seal, extended operating temperature, and robust design make this headset ready for action in virtually any fireground environment. The single slotted dome does not provide hearing protection.

Transmit Receive Intercom Yes Yes Radio PTT Yes



FEATURES

State-of-the-art ear and hearing protection

- ComLeather over memory foam ear seals for hours of comfortable use
- Enhanced durability and comfort, designed to fit any head size
- IP65 rating for dust/water protection when worn

Enhanced microphone

- Flexible mic. boom with slide adjustment for accurate/secure positioning
- Microphone boom rotates for left or right dress
- Noise-cancelling electret microphone ensures optimal clarity
- Programmable microphone gain
- Microphone protected by a layer of waterproof material for outdoor use
- Microphone muff improves clarity by eliminating wind noise

Total configurability

- Full duplex intercom plus listen-only radio in intercom mode
- Communicates over radio with push-and-hold transmit button
- PTT button requires solid push, eliminating accidental transmissions
- Fully programmable to user specifications

Simple maintenance

- Black domes for easy cleaning
- Black powder-coated headband for durability
- Glove-rugged plug for longer life

SPECIFICATIONS

Physical

Weight: 19 oz.

Color: Black

Environmental

- IP-65 rated, when worn
- Operating temperature
 -40°F (-40°C) to +158°F (+70°C)
- Storage temperature -40°F (-40°C) to +185°F (+85°C)
- Charging Temperature
 32°F (0°C) to +104°F (+40°C)

SAE

Salt Spray per J1455, Sec. 4.3

ISO

 Conducted Transients per 7637-2

MIL

- Humidity per MIL-STD 810F and 810G
- Temperature Shock per MIL-STD 810F and 810G
- Chemical Exposure per MIL-STD 810F and 810G

