

### FIRECOM 50 SERIES WIRED

#### **UH-52** UNDER-HELMET STYLE HEADSET

The Firecom UH-52 wired headset delivers all the benefits of hands-free, full-duplex communication with your crew. Operating with a stand-alone intercom system or integrated with a mobile radio, the flexible design brings all crew members into constant communication. Behind-the-head band configuration with adjustable over-head strap easily accommodates use with helmets. Water-resistant and comfortable ear seals, extended operating temperature, and robust design make this headset ready for action in virtually any fireground environment.

# Transmit Receive Intercom PTT Yes Radio Yes



#### **FEATURES**

## State-of-the-art ear and hearing protection

- ComLeather over memory foam ear seals for hours of comfortable use
- Enhanced durability and comfort, designed to fit any head size
- 24dB noise reduction rating (NRR)
- IP65 rating for dust/water protection when worn

#### **Enhanced microphone**

- Flexible mic. boom with slide adjustment for accurate/secure positioning
- Microphone boom rotates for left or right dress
- Noise-cancelling electret microphone ensures optimal clarity
- · Programmable microphone gain
- Microphone protected by a layer of waterproof material for outdoor use
- Microphone muff improves clarity by eliminating wind noise

#### **Total configurability**

- Push-totalk intercom plus listen-only radio
- Communicates over radio with push-to-talk transmit button
- PTT button requires solid push, eliminating accidental transmissions
- Fully programmable to user specifications

#### Simple maintenance

- Black domes for easy cleaning
- Black powder-coated headband for durability
- Glove-rugged plug for longer life

#### **SPECIFICATIONS**

#### **Physical**

- Weight: 19 oz.
- Color: Black
- Noise Reduction Rating: 24dB NRR

#### **Environmental**

- IP-65 rated, when worn
- Operating temperature
   -40°F (-40°C) to +158°F (+70°C)
- Storage temperature -40°F (-40°C) to +185°F (+85°C)
- Charging Temperature
   32°F (0°C) to +104°F (+40°C)

#### **SAE**

 Salt Spray per J1455, Sec. 4.3

#### ISO

 Conducted Transients per 7637-2

#### MIL

- Humidity per MIL-STD 810F and 810G
- Temperature Shock per MIL-STD 810F and 810G
- Chemical Exposure per MIL-STD 810F and 810G

