

APX379.v2

DECT7 WIRELESS HEADSET WITH ADVANCED HEARING PROTECTION & BLUETOOTH®

The Sonetics APX379 wireless headset allows you to have a hands-free conversation with your team without having to shout. The headset protects you from dangerous noise levels while automatically adjusting audio to a comfortable listening level.

Listen-Through allows you to hear what's happening around you, so you can stay aware of alarms, warnings, or have a face-to-face conversation with someone without a headset. Simultaneously take calls, listen to music, or even integrate a two-way radio via wired or Bluetooth inputs. Engineered and tested for rugged durability in extreme environments, the APX379 improves team communication no matter where you work.



DECT7® WIRELESS COMMUNICATIONS¹

Clear, wireless communication for 2 to 20 users with up to 1600-foot (line of sight) range in high-definition, wideband audio.



DECT7 MULTI-CHANNEL²

One-to-many channels; headsets scale to your team.



BLUETOOTH - ENABLED

Make a phone call, listen to music, or talk on your radio wirelessly via Bluetooth.



RADIO TRANSMIT

Direct-wire interface with any portable radio with a Sonetics PR Adapter (sold separately).



RUGGED

Built to withstand environmental extremes, the APX379 is dust-proof and watertight.



LISTEN-THROUGH

Stereo Listen-Through allows you hear what's going on around you while protecting your ears from dangerous noise levels.



AUTOMATIC LOUD NOISE SUPPRESSION

The APX379 automatically limits high impulse noises such as gunshots from being transmitted to the user in Stereo Listen-Through mode.



NOISE CANCELLING MICROPHONE

Be understood even in the loudest environments.



AUTO-LEVELING MICROPHONE

Be heard clearly as you move from low to high-noise areas.



HEARING PROTECTION

Passive noise reduction eliminates unsafe noise.

¹ Requires Sonetics DECT Base, ComHub or MiniHub.

² Requires multi-channel DECT or IP-DECT Base, ComHub or MiniHub.

CONVERTIBLE HEADBAND

Easily convert from over the head to behind head styles.



Behind Head



Over The Head



Hardhat Adapters
* Sold separately

CHOOSE YOUR COLOR

Personalize and identify with silicone ruggedizers.



APX379.v2

CLEAR COMMUNICATION IN HIGH-NOISE ENVIRONMENTS

FEATURES

MOBILE DEVICE AND RADIO CONNECTIVITY

Bluetooth A2DP audio streaming

Connect to your MP3 player or phone directly via the auxiliary jack

Make calls or listen to music while you work

ROBUST DESIGN

Flexible microphone boom

2-stage microphone cover eliminates wind noise

Enhanced durability and comfort; designed to fit any head size

IP66 Rating - dust-proof and sealed against salt spray and moisture

Microphones protected by a layer of waterproof material for outdoor use

High strength, tough, fatigue-resistant polymer for headband durability

STATE-OF-THE-ART HEARING PROTECTION

Sound suppressor reduces loud noise while enhancing other sounds

Stereo Listen-Through microphones allow face-to-face conversation and situational awareness

24dB passive noise reduction rating (NRR)

LONG-LASTING POWER SOURCE

24-hour rechargeable lithium-ion battery

User-replaceable battery

Energy-saver sleep mode: one year of shelf life without losing charge

Simple on/off operation

Power-on battery capacity LED indicator

Audible and visual 2-stage low battery warning

110/220V DC battery charger included

Heavy-duty 12V DC charging cable included

TOTAL CONFIGURABILITY

Features are custom programmable to user specifications

Programmable microphone gain

Voice prompts for easy feature navigation and feedback

CUSTOMIZABLE

Easily configures to over-the-head, under-helmet or hardhat clip-mounted styles

Personalize and protect with silicone ruggedizers (available in 12 standard colors)

APEX 3-SERIES HEADSETS

Model	Mic	Bluetooth	DECT7
APX379	✓	✓	✓
APX377	✓		✓

SPECIFICATIONS

DECT7 WIRELESS TECHNOLOGY

Dynamic channel allocation

DECT Standard Cipher with 35-bit initialization vector

Frequency Bandwidth: 1920 MHz to 1930 MHz

BLUETOOTH TECHNOLOGY

Bluetooth 3.0 with secure simple pairing

Frequency: 2400 MHz-2485 MHz

Power: 2.4 mW / 4 dBm

PHYSICAL

Weight: 16 oz. (without ruggedizers)

Color: Black

Noise Reduction Rating: 24dB NRR

Side Pressure: 2.2 lbs.

POWER

3.7V rechargeable lithium-ion battery (18650 replaceable)

More than 24 hours of battery life at 77°F (25°C)

Charge time: 4 hours

AC Charge Source: supplied 12V, 500mA wall charger

DC Charge Source: 5V to 16V, 1.5A minimum, cable supplied

Over voltage, under voltage, over current and over temperature protection

ENVIRONMENTAL

IP66 Rating

Operating temperature -22°F (-30°C) to 140°F (60°C)

Storage temperature -40°F (-40°C) to +185°F (+85°C)

MIL

Humidity per MIL-STD 810F and 810G

Temperature Shock per MIL-STD 810F and 810G

Chemical Exposure per MIL-STD 810

SAE

Salt Spray per J1455, Sec. 4.3

Vibration per J1455, Sec. 4.9

Conducted Immunity per J1113-11

Electrostatic Discharge per J1113-13

Radiated Emissions per J1113-41

ISO

Conducted Transients per 7637-2

Quality Management System ISO 9001:2015

Sonetics®

Sonetics.com | 800-833-4558

17600 SW 65th Ave,
Lake Oswego, OR 97035 USA

SON-PS-0018-A